


Accident avoidance by active intervention for Intelligent Vehicles



interactIVe - accident avoidance by active intervention for Intelligent Vehicles

Adrian Zlocki, Felix Fahrenkrog Institut für Kraftfahrzeuge, RWTH Aachen University

20th ITS World Congress Tokyo 2013 18th October 2013




SP7 "Evaluation and legal aspects" - Overview

SP7 role in interactIVe:

- Definition of a test and evaluation framework
- Development of test scenarios, procedures and evaluation methods
- Provision of tools (e.g. equipment, test catalogues, questionnaires or software) and test support
- Definition of test and evaluation criteria
- Analysis of legal aspects

Evaluation divided into:

- Technical assessment (on function level)
- User-related assessment
- Impact assessment






SP7 "Evaluation and legal aspects" - Methodology

Methodology for the evaluation bases mainly on the PReVAL methodology:

- Step 0: System and function description
- Step 1: Expected impact and hypotheses
- Step 2: Test scenario definition

- Step 3: Evaluation method selection
- Step 4: Measurement plan
- Step 5: Test execution and analysis •




Adaptation and application of methodology in interactIVe

Techncial Assessment – Example Results

- Overall 908 test runs considering 8 accident related test scenarios (e.g. rear-end, blindspot or run-off road conflicts) were evaluate to analyse the defined hypotheses
- In general the interactIVe functions behave in the intended way
- Considering the activation behaviour at least some function are still in the research phase

• Example:

Hyp_T_gen_TecU_01: The driver has enough time to react and avoid the accident, when the warning is issued



The remaining reaction time is (TTC @ warning - t_{Manoeuvre}) compared to the presumed reaction time s
 Hypothesis is confirmed at significance level of 5% at a reaction time of t_{Reaction} = 1.2 s in the example on the left


Hypothesis is confirmed at significance level of 5% at a reaction time of t_{Reaction} = 1.0 s in the example on the right



User-related Assessment – Results

- For the user-related assessment 9 studies with 263 test person have been conducted
- Method chosen depending on the criticality of the system under investigation
 - Small field test
 - Focus group studies
 - Tests on a test track
 - Driving simulator studies





Interactive


Source: Ford

Source: VTEC


User-related Assessment – Example Results

Intended usage of the functions

CS: Continuous Support **RECA**: Rear-end Collision Avoidance **CMS**: Collision Mitigation System



Motorways




- The test persons would use interactIVe functions frequently
- Drivers would use the function more on motorways and less in urban regions exception CMS



User-related Assessment – Example Results

• Willingness to pay

CS: Continuous Support **RECA**: Rear-end Collision Avoidance **CMS**: Collision Mitigation System



• The test persons are not willing to spend much money on active safety functions (< 500 €)

• The test persons are willing to pay more for functions that intervene than for functions which only warn




Safety Impact Assessment – Methodology

- Literature review on impact assessment methodologies:
 - Safety Mechanisms
 - Accident Reconstruction
 - Neural Network
 - FOT Approach
- Chose appropriate methodology by considering the available data as well as advantage and disadvantages of the methodologies:
 - Nine Safety Mechanisms


- Direct effects
 - 1. Direct in-car modification of the driving task,
 - 2. Dir Only in-car functions cations,
- Indirect effects on user
 - 3. Indirect modification of user behaviour,
- Effects on non-users
 - 4. Indirect modification of non-user behaviour,
 - 5. Modification of interaction between users and non-users,
- Exposure effects
 - ^{6.} Exposure effects, typically
 - 7. Modification of modal phoice
 - 8. Modification of route choice,
- Effects on post-accident consequence modification
 - 9. Mod Only post-collision uences.



Direct effects - Rear-end scenario (Braking)



Direct effects - Rear-end (collision mitigation)




• Use known relations between Δv in order to calculate injury risk...



Safety Impact Assessment – Example (Preliminary) SP7 Results

- Sample result for a rear-end collision avoidance function:
 - 364 in-depth rear end accident scenarios analyzed
 - 77 % collision avoided
 - 22 % collision mitigated
 - 1 % no effected
- Sample result for a collision mitigation function:
 - 364 in-depth rear end accident scenarios analyzed
 - 34 % collision avoided
 - 42 % collision mitigated
 - 24 % no effected



Summary & Next steps

- A test and evaluation framework was defined, which considers test plans and test methods for all 11 interactIVe functions
- The interactIVe functions have been tested and evaluated in the technical and user-related assessment
- Based on the results a safety impact assessment of the interactIVe functions were conducted

Final Event:

- 20-21 November 2013 in Aachen
- Joint event with eCoMove
- November 20: Presentations & Exhibition in Aachen
- November 21: Demo drives on Ford Proving Ground in Lommel
- Subscription is open at the interactIVe website: http://interactive-ip.eu





Accident avoidance by active intervention for Intelligent Vehicles

www.interactlVe-ip?eu

Thank you.

Co-funded and supported by the European Commission





SEVENTH FRAMEWORK PROGRAMME